



▶ **Scanning Stage SCAN 75 x 30** for upright microscopes

	Specification
Travel range:	max. 75 x 30 mm
Repeatability:	< 1 µm* measured according to VDI / DGQ 3441
Accuracy:	+/- 3 µm* measured according to VDI / DGQ 3441
Orthogonality:	< 20" *
Resolution:	0,05 µm* (smallest step size)
Max. travel speed:	60 mm/s*, with 1 mm lead screw pitch 120 mm/s*, with 2 mm lead screw pitch
Motor:	2-phase stepper motor
Material:	aluminium
Limit switches:	optical light beam
Weight:	3.800 g
Surface:	anodic coating, black
Certification:	DIN EN ISO 9001 : 2000
Packaging type:	protective polyurethane foam
Packaging size / type:	58 x 48 x 38 cm / 8 kg

* Specification valid with Märzhäuser stage controller only

Specifications subject to change without notice.

Order Informationen

Part No.: 96-24-561-0000, with 1 mm lead screw pitch

Part No.: 96-24-562-0000, with 2 mm lead screw pitch

Features

- ▶ for upright microscopes
- ▶ flat design due to lowered motor axis
- ▶ for reflected light and transmitted light applications
- ▶ exchangeable stage inserts for different kinds of applications
- ▶ The integrated electronic stage identification device ETS enables automatic identification of the scanning stage as well as the parametrization of the controller.
- ▶ 5 years guarantee, if the scanning stage is operated in the system with the Märzhäuser TANGO controller!
- ▶ motor cable connection front right

Accessories

Stage insert for slide 3" x 1"

Part No.: 00-29-401-8010

Glass plate

Part No.: 00-24-401-0810

Metal plate

Part No.: 00-24-401-0011